

TECHNICAL DATASHEET

506U040405

Rev.00



FEATURES:

- New technical features and design
- Panoramic wrapping lens available with AF+ and AS+ coatings
- Temples regulation in length and inclination
- Soft terminal tips to eliminate local pressure
- Optimal comfort and fit thanks to the soft adjustable nosepad
- New range of colours

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40°
Temple adjustment	Inclination and Length
Weight (g)	25
Size (mm)	136 119-126
Material Features	Latex free

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Green
Technical Treatment	Antiscratch
Aesthetic Treatment	-
Thickness [mm](+/- 0.1)	2.3
Curvature	Base 9 Spheric
Optical Class	1
UV Protection	400 nm
Spare Parts	-
VLT% (+/-5%)	9.3

MARKING DATA:

Standard References	EN166 EN170 EN172
Frame Marking	Mod.506U U EN166 FT CE
Ocular/Flip-up Marking	2C-3/5-3.1 U 1 FT CE

APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T)

Notes

