

TECHNICAL DATASHEET

5X6031100

Rev.00



FEATURES:

- Sporty and wrap-around design
- Lens with FLD (Floating Lens Design) technology
- SoftPad technology
- Light and comfortable device, ideal for prolonged use
- Adjustment of temples in length
- Adjustable soft and anatomical nose pad

FRAME FEATURES:

Frame Typology	Spectacle
PPE field of view	>40°
Temple adjustment	Length
Weight (g)	26
Size (mm)	139 118 - 134

Material Features **Anallergic**

FEATURES OCULARS/LENSES:

Ocular/Flip-up Material	Polycarbonate
Colour	Clear
Technical Treatment	Antifog PLUS Antiscratch PLUS
Aesthetic Treatment	-
Thickness [mm](+/- 0.1)	2.1
Curvature	Base 6.5 Spheric
Optical Class	1
UV Protection	400 nm
Spare Parts	-
VLT% (+/-5%)	88,8

MARKING DATA:

Standard References	EN166 EN170
Frame Marking	Mod.5X6 U EN166 FT CE
Ocular/Flip-up Marking	2C-1.2 U 1 FT K N CE

APPLICATION FIELDS

Protection against high-speed particles 45 m/s - low energy (F); Protection against high-speed particles at extreme temperatures (T); Resistance to fogging of oculars (N); Resistance to surface damage by fine particles (K)

Notes

